



EC Declaration of Conformity

We hereby declare that the following product is in conformity with the requirements of the following EC Directives:

Product: Type D4N, D4N-R, D4NH Series
Safety Limit Switch, Safety Door Hinge Switch
with Direct Opening Action

No. of Directive : 2006/42/EC including amendments
Title of Directive : Machinery Safety Directive

This product is designed and manufactured in accordance with the following standards:

Machinery safety : EN60947-5-1: 2004
EN1088: 1995+A2: 2008 clause 6.2.1.2,
EN115: 1995+A2: 2004, clause 14.1.2.2

Description of Product


These devices feature direct opening action according to EN60947-5-1 and are intended for safety-related application in machinery.

Year of CE marking : 2003

Manufacturer :

Name : Omron Corporation,
Industrial Automation Company,
Business Development Dept. Safety Division
Address : Shiokoji Horikawa, Shimogyo-ku, Kyoto, 600-8530 Japan


Date : 12. 11, 2009

Signed : 
Yoshinori Matsueda
Manager

Representative in EU:

Name: Omron Europe B.V.
Address: Zilverenberg 2, 5234 GM s Hertogenbosch, The Netherlands

Date: 15. 12, 2009

Signed: 
Hugo Sintnicolaas
European Manufacturing and Quality Manager

List of EC Declaration of Conformity

Type: D4N, D4N-R, D4NH series

[illegible]



Product Service

CERTIFICATE

No. B 09 10 39656 192

Holder of Certificate: **Omron Corporation**

Shiokoji Horikawa, Shimogyo-ku
Kyoto
600-8530 JAPAN

**Production
Facility(ies):**

23708, 56891

Certification Mark:**Product:**

**Limit Switches
Limit Switch with / without Direct Opening Action**

Model(s):

**D4N II-III IV V VI-VII
(See Attachment 1 for Nomenclature)**

Parameters:

AC: 240 VAC / 3A, 50-60 Hz (AC-15)
DC: 250 VDC / 0,27A (DC-13)
See Suffix VII of attached nomenclature

Protection class: II
Protection degree: IP67 (IP65 for D4NA series only)
Pollution degree: 3
Overvoltage category: III
Conditional Short Circuit Current: 100 A
Electrical durability: 150000 Cycles
Mechanical durability: 1000000 Cycles
See Suffix V of attached nomenclature

Remark:

1. Meets the requirements of GS-ET-15:2005
2. When installing/inserting the equipment all requirements of the mentioned test standard must be fulfilled.

Tested according to: EN 60947-5-1:2004

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

Test report no.: 73508741**Date,** 2009-10-30

Page 1 of 3

(Shigehisa Ishikawa)



Certificate Attachment 1
Certificate No.



Product Service

B 09 10 39656 192

TYPE NOMENCLATURE: Nomenclature of Body

D4N □ — 1 A 11 □ — #
I II III IV V VI VII

I: Basic type

II: With or without lever shaft for door hinge

Blank: Without lever shaft
A: Without lever shaft (for the production in China)
H: With lever shaft for door hinge

III: Conduit Variation

1:	Pg13.5	(1 Conduit)
2:	G1/2	(1 Conduit)
3:	1/2-14NPT	(1 Conduit)
4:	M20	(1 Conduit)
5:	Pg13.5	(2 Conduits)
6:	G1/2	(2 Conduits)
7:	1/2-14NPT	(2 Conduits)
8:	M20	(2 Conduits)
9:	M12	(1 Conduit, with Plug)
A:	M12	(2 Conduits, with Plug)
B:	M12	(1 Conduit, with Connector)
C:	M12	(2 Conduits, with Connector)

IV: Switch Mechanism

1:	1NC/1NO	(Snap action)
2:	2NC	(Snap action)
A:	1NC/1NO	(Slow action)
B:	2NC	(Slow action)
C:	2NC/1NO	(Slow action)
D:	3NC	(Slow action)
E:	1NC/1NO (Make Before Break)	(Slow action)
F:	2NC/1NO (Make Before Break)	(Slow action)
G:	2NO	(Slow action)

Certificate Attachment 1
Certificate No.



Product Service

B 09 10 39656 192

V: Actuator

20:	Roller lever	(R26 / plastic lever / plastic roller)	
21:	Adjustable roller lever	(R20 to R65 / metal lever / plastic roller)	
22:	Roller lever	(R26 / metal lever / plastic roller)	
23:	Roller lever	(R28 / metal lever / plastic roller)	
25:	Roller lever	(R26 / metal lever / metal roller)	
26:	Roller lever	(R26 / metal lever / bearing roller)	
27:	Adjustable roller lever	(R31 to 65 / metal lever / rubber roller)	
28:	Adjustable roller lever	(R31 to 80 / metal lever / rubber roller)	
29:	Rod lever		
2B:	Adjustable roller lever	(R20 to 66 / metal lever / plastic roller)	
2G:	Adjustable roller lever	(form lock / R20 to 66 / metal lever / plastic roller)	
2H:	Adjustable roller lever	(form lock / R32 to 66 / metal lever / rubber roller)	
2J:	Roller lever	(R26 / metal lever / plastic long roller)	
2L:	Adjustable roller lever	(form lock / R20 to 66 / metal lever / metal roller)	
31:	Plunger		
32:	Roller plunger		
34:	Metal roller plunger		
62:	One way roller lever	(R20 / Ø12 x 5mm)	(horizontal)
63:	One way roller lever	(horizontal)	
64:	One way roller lever	(R14,9 / Ø14 x 5mm)	(horizontal) * See Note 1
72:	One way roller lever	(vertical)	
80:	Wobble lever		
87:	Wobble lever plastic rod		
RE:	Right side, Fork lever lock	(R26 / rubber roller)	
LE:	Left side, Fork lever lock	(R26 / rubber roller)	
AS:	Rotary shaft (Ø8,5 hole)	* See Note 2	
AS1:	Rotary shaft (Ø6 x 15mm)	* See Note 2	
BC:	Center lever	* See Note 2	

* Note 1) Mechanical Durability is 3000000 operations

* Note 2) Mechanical Durability is 1000000 operations

VI: With or without reset button

Blank: Without reset button

R: With reset button

VII: Customer Code

Blank: Standard

GP: Special code for model connected with Connector type XS2W-D421

#: Customer code

Maximum 6 digit number(s) and/or letter(s) except for GP

* Note) Rated voltage and current for D4N-9xxx-GP: 120VAC/3A (AC-15), 125VDC/0.22A (DC-13)



NKCR.E76675 Auxiliary Devices

[Page Bottom](#)

Auxiliary Devices

[See General Information for Auxiliary Devices](#)

OMRON CORP

E76675

SAFETY STANDARDS GROUP
IAB QUALITY & ENVIRONMENT DEPT
SHIOKOJI HORIKAWA, SHIMOGYO-KU
KYOTO, 600-8530 JAPAN



Trademark and/or Tradename:

Door lock switch, Type D4GL followed by 1, 2, 3 or 4, followed by A through H or J through M, followed by B, F, L, R, D, E, G or H, followed by A, G or N, may be followed by A, B or C, may be followed by 4, may be followed by N, may be followed by additional letter(s) and/or number(s).

Door switches, Type D4BS followed by 1, followed by 1, followed by B, F, L or R, followed by S, followed by F, followed by 1, may be followed by additional letter(s) and/or number(s).

Type D4BL Series followed by 1, 2, 3, or 4, followed by C, D, E or F, followed by A, B, C, D, E, F or G, followed by blank, A, B, C, D, E or F, followed by blank, 12-30 or T, followed by blank or maximum 6 digits of letters and/or numbers.

Type D4GS may be followed by 1, 2, 3 or 4, may be followed by up to two letters and/or numbers, may be followed by up to six letters and/or numbers.

Type D4GS-N followed by 1, 2, 3 or 4, followed by R or T, may be followed by 3, 5 or up to two letter and/or numbers, may be followed by up to six letters and/or numbers.

Type D4GS-NK followed by 1, 2 or 4, may be followed by E, may be followed by up to six letters and/or numbers.

Type D4NL followed by 1, 2, 3 or 4, followed by A through H, J through N or P, followed by B, D, E, F, G, L or R, followed by A, B, C, D, E, F, G, H, J, K or L, may be followed by A through F, may be followed by 4, may be followed by S, may be followed by Z, may be followed by additional letter(s) and/or number(s).

Type D4NS followed by 1 through 9 or A, B or C, followed by A through F, followed by B, D, E, F, G, H, L or R, may be followed by additional letter(s) and/or number(s).

Type D4N may be followed by A or H, followed by 1 through 9 or A, B or C, followed by 1, 2 or A through G, followed by 20, 21, 21-TK, 22 through 29, 2B, 2C, 2D, 2G, 2H, 2J, 2L, 31, 32, 34, 62, 63, 72, 80, 87, RE, LE, AS, BC or AS1, may be followed by R, may be followed by additional letter(s) and/or number(s).

Type D4N, followed by blank, followed by 9, followed by 1, followed by 20, followed by GP.

Type D4JL, followed by 1, 2, 3 or 4, followed by A through H, J through N or P through R, followed by D or F, followed by A, G or K, followed by C or D, followed by 5, 6 or 7, followed by blank, followed by blank, Y or Z, may be followed by four alphanumeric code, may be followed by six digit maximum alphanumeric code.

Interlock relay, Cat. No. D9MCD1.

Limit switches, Type D4C may be followed by C, followed by 1, 2, 3, 4, 5 or 6, may be followed by additional suffix numbers.

Type D4C followed by 10, 20, 30, A0, C0 or D0, followed by a two digit number, followed by DRAJ01 or ARAJ01, may be followed by additional letters and/or numbers.

Type D4BS followed by -1, -2, -3, -4, -5, -6, -7 or -8, followed by 5, 6, 7, 8, A or B, followed by F, R, L or B, followed by S, may be followed by LD or LE, may be followed by additional numbers and/or letters.

Type D4A receptacle Cat. No. D4A- followed by 1000N through 6000N, 1000, 2000, 3000, 4000, 5000 or 6000, may be followed by additional numbers and/or letters; actuator head Cat. No. D4A-00 followed by 01N through 06N, 07-VN, 07-HN, 08N through 12N or 14N through 20N or 24N, may be followed by additional letters and/or numbers; body Cat. No. D4A-0 followed by 100N, 300N, 500N, 700N or 900N, may be followed by additional numbers and/or letters.

Type D4F followed by 1 through 5, followed by 0 or 2, followed by 0, 2, 3, G or H, followed by a number, followed by R, L or D, may be followed by letters and/or numbers.

Type D4A, followed by 3, may be followed by E, followed by 01-06, 07-V, 07-H, 08-12, 14-20 or 24, may be followed by N, followed by GM or KGM, may be followed by additional letter(s) and/or number(s).

Type SHL, followed by D, Q or W, with or without 1 or 2 digit number, followed by 55, followed by blank, followed by blank, L, L6 or L7, followed by blank, MD, ML or MR, followed by blank, 2 or 3, followed by blank, TC or TH, followed by blank or 11; followed by blank or T; followed by blank or up to six additional letters and/or numbers.

Type WL may be followed by R, may be followed by 01, may be followed by A or B, may be followed by M, followed by C#, D#, G#, H#, NJ# or SD#, where # is up to a ten digit symbol of letters and/or numbers, may be followed by 10, 31 or RP, may be followed by P1, may be followed by 55, may be followed by T, TC, TC2 or TH, may be followed by 13##, 14##, RP4##, RP5## or RP6##, where ## is a one or two digit symbol of letters and/or numbers, may be followed by C, G, G1, TS or Y, may be followed by LD, LDN or LE, may be followed by A or F, may be followed by S, may be followed by DGJS03, DGJ###, DK1CJ###, DK1EJ###, M1J###, M1GJ###, M5J###, DHJS###, AGJ###, AK1EJ####, AK1J###, AK4EJ### or K###, where ### is up to a five digit symbol of letter(s) and/or number(s), may be followed by up to a five digit symbol of letters and/or numbers.

Type WL, may be followed by R, followed by C, D, G, H, NJ, or SD, followed by a number, may be followed by LD, followed by GM, KGM or K-GM, may be followed by additional letter(s) and/or number(s).

Type D4B-F, followed by 1, 2, 3 or 4, followed by 1, 2 or 3, followed by 11, 15, 1F or 1R, followed by F, may be followed by 1, followed by additional letter(s) and/or number(s).

Types ZE, ZV, ZV2 may be followed by -01 or Y, followed by N or Q, followed by 6 letters and/or numbers, may be followed by 2, may be followed by G, G1, S or Y, may be followed by TC or TH, may be followed by additional letters and/or numbers.

Type D4B followed by -1, -2, -3, -4, -5, -6, -7 or -8, followed by 1, 2, 3, 4, 5, 6, 7, 8, A, B, C or D, followed by 1 thru 8 or 00, may be followed by up to two numbers or letters, followed by N, may be followed by LD or LE, may be followed by letters and/or numbers.

Magnetically actuated interlock switches, Models D40B-J1X, -J2X.

Magnetically actuated switches, Cat. Nos. D40B-1B3, D40B-1B10, D40B-1D3, D40B-1D10, D40B-A1, D40B-S1B3, D40B-S1B10, D40B-S1D3, D40B-S1D10, D40B-2B3, D40B-2B10, D40B-2D3, D40B-2D10, D40B-A2, D40B-S2B3, D40B-S2B10, D40B-S2D3, D40B-S2D10, D40B-3D5C, D40B-3E5C, D40B-A3, D40B-S3D5C, D40B-S3E5C, D40B-J1, D40B-J2.

Non-contact safety door switch, Model(+) D40A-1C followed by 2 or 5.

Non-contact door switch, Actuator only Model D40A-A1.

Non-contact door switch, Sensor only Model D40A-S1C followed by 2 or 5.

Pendant enable switch, Model A4EG- followed by B or C, followed by 00, E1, E2, M2, P1 or P2, followed by 0, B, R, Y or G, followed by 0, followed by 1, 2 or 4, followed by 0 or 1, may be followed by A, may be followed by letters B through Z, b through z, and/or numbers.

Thermal overload relays, Cat. Nos. J7TL-D2, -E2, -F2, J7TL-D, -E, -F, -A, -B, -C.

Terminal relay, Model F3SP-T01.

(+) = Additional functional safety investigation was completed to UL 991 and IEC 60947-5-3.

Last Updated on 2009-10-22

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2010 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2010 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.





NKCR7.E76675 Auxiliary Devices Certified for Canada

[Page Bottom](#)

Auxiliary Devices Certified for Canada

[See General Information for Auxiliary Devices Certified for Canada](#)

OMRON CORP

E76675

SAFETY STANDARDS GROUP
IAB QUALITY & ENVIRONMENT DEPT
SHIOKOJI HORIKAWA, SHIMOGYO-KU
KYOTO, 600-8530 JAPAN

Auxiliary contact blocks, Cat. Nos. J73L-B, J73L-C, J7L-BR.

Door lock switch, Type D4GL followed by 1, 2, 3 or 4, followed by A through H or J through M, followed by B, F, L, R, D, E, G or H, followed by A, G or N, may be followed by A, B or C, may be followed by 4, may be followed by N, may be followed by additional letter(s) and/or number(s).

Door switches, Type D4BL Series, followed by 1, 2, 3, or 4, followed by C, D, E or F, followed by A, B, C, D, E, F, or G, followed by blank, A, B, C, D, E, or F, followed by blank, 12-30, or T, followed by blank or maximum 6 digits of letters and/or numbers.

Type D4GS may be followed by 1, 2, 3, or 4, may be followed by up to two letters and/or numbers, may be followed by up to six letters and/or numbers.

Type D4GS-N followed by 1, 2, 3 or 4, followed by R or T, may be followed by 3, 5 or up to two letter and/or numbers, may be followed by up to six letters and/or numbers.

Type D4GS-NK followed by 1, 2 or 4, may be followed by E, may be followed by up to six letters and/or numbers.

, Type D4BS followed by 1, followed by 1, followed by B, F, L or R, followed by S, followed by F, followed by 1, may be followed by additional letter(s) and/or number(s).

Hand mixer, Model KJ-805.

Interlock relay, Cat. No. D9MCD1.

Limit switches, Type D4B-F, followed by 1, 2, 3 or 4, followed by 1, 2 or 3, followed by 11, 15, 1F or 1R, followed by F, may be followed by 1, followed by additional letter(s) and/or number(s).

Cat. No. D4C may be followed by C, followed by 1 or 2, may be followed by additional number or letters.

Type D4C may be followed by C, followed by 1, 2, 3, 4, 5 or 6, may be followed by additional suffix numbers.

Type D4C followed by 10, 20, 30, A0, C0 or D0 followed by a two digit number, followed by DRAJ01 or ARAJ01, may be followed by additional letter(s) and/or numbers.

Type D4BS followed by -1, -2, -3, -4, -5, -6, -7 or -8, followed by 5, 6, 7, 8, A or B, followed by F, R, L or B, followed by S, may be followed by LD or LE, may be followed by additional numbers and/or letters.

Type D4A, Receptacle Cat. No. D4A- followed by 1000N through 6000N, 1000, 2000, 3000, 4000, 5000 or 6000, may be followed by additional numbers and/or letters; Actuator head Cat. No. D4A-00 followed by 01N through 06N, 07-HN, 07-VN, 08N through 12N or 14N through 20N or 24N, may be followed by additional letters and/or numbers; Body Cat. No. D4A-0 followed by 100N, 300N, 500N, 700N, 900N, may be followed by additional numbers and/or letters.

Type D4A, followed by 3, may be followed by E, followed by 01-06, 07-V, 07-H, 08-12, 14-20 or 24, may be followed by N, followed by GM or KGM, may be followed by additional letter(s) and/or number(s).

Type D4F, followed by 1 through 5, followed by 0 or 2, followed by 0, 2, 3, G or H, followed by a number, followed by R, L or D, may be followed by additional letters and/or numbers.

Type SHL, followed by D, Q or W, with or without 1 or 2 digit number, followed by 55, followed by a blank, followed by blank, L, L6 or L7, followed by blank, MD, ML or MR, followed by a blank, 2 or 3, followed by a blank, TC or TH, followed by blank or 11, followed by blank or T; followed by a blank or up to six additional letters and/or numbers.

Type WL may be followed by R, may be followed by 01, may be followed by A or B, may be followed by P, followed by C#, D#, G#, H#, NJ# or SD#, where # is up to a ten digit symbol of letters and/or numbers, may be followed by 10, 31 or RP, may be followed by P1, may be followed by 55, may be followed by T, TC, TC2 or TH, may be followed by 13##, PR4##, PR5## or RP6##, where ## is a one or two digit symbol of letters and/or numbers, may be followed by C, G, G1, TS or Y, may be followed by LD, LDN or LE, may be followed by A or F, may be followed by S, may be followed by DGJS03, DGJ####, DK1CJ####, DK1EJ####, M1J####, M1GJ####, M5J####, DHJS####, AGJ####, AK1EJ####, AK1J####, AK4EJ#### or K####, where ### is up to a five digit symbol of letter(s) and/or number(s), may be followed by up to a five digit symbol of letters and/or numbers.

Type WL, may be followed by R, followed by C, D, G, H, NJ, or SD, followed by a number, may be followed by LD, followed by GM, KGM or K-GM, may be followed by additional letter(s) and/or number(s).

Types ZE, ZV, ZV2 may be followed by -01 or Y, followed by N or Q, followed by six letters and/or numbers, may be followed by 2, may be followed by G, G1, S or Y, may be followed by TC or TH, may be followed by additional letters and/or numbers.

Type D4B followed by -1, -2, -3, -4, -5, -6, -7 or -8, followed by 1, 2, 3, 4, 5, 6, 7, 8, A, B, C or D, followed by 1 thru 8 or 00, may be followed by up to two numbers or letters, followed by N, may be followed by LD or LE, may be followed by letters and/or numbers.

Magnetically actuated switches, Cat. Nos. D40B-1B3, D40B-1B10, D40B-1D3, D40B-1D10, D40B-A1, D40B-S1B3, D40B-S1B10, D40B-S1D3, D40B-S1D10, D40B-2B3, D40B-2B10, D40B-2D3, D40B-2D10, D40B-A2, D40B-S2B3, D40B-S2B10, D40B-S2D3, D40B-S2D10, D40B-3D5C, D40B-3E5C, D40B-A3, D40B-S3D5C, D40B-S3E5C, D40B-J1, D40B-J2.

Non-Contact Safety Door Switch, Model(+) D40A-1C, followed by 2 or 5.

Non-contact door switch, Actuator only Model D40A-A1.

Non-contact door switch,,, Sensor only Model D40A-S1C followed by 2 or 5.

Pendant enable switch, Model A4EG- followed by B or C, followed by 00, E1, E2, M2, P1 or P2, followed by 0, B, R, Y or G, followed by 0, followed by 1, 2 or 4, followed by 0 or 1, may be followed by A, may be followed by letters B through Z, b through z, and/or numbers.

Switches, Type D4NL followed by 1, 2, 3 or 4, followed by A through H, J through N or P, followed by B, D, E, F, G, L or R, followed by A, B, C, D, E, F, G, H, J, K or L, may be followed by A through F, may be followed by 4, may be followed by S, may be followed by Z, may be followed by additional letter(s) and/or number(s).

Type D4NS followed by 1 through 9 or A, B or C, followed by A through F, followed by B, D, E, F, G, H, L or R, may be followed by additional letter(s) and/or number(s).

Type D4N may be followed by A or H, followed by 1 through 9 or A, B or C, followed by 1, 2 or A through G, followed by 20, 21, 21-TK, 22 through 29, 2B, 2C, 2D, 2G, 2H, 2J, 2L, 31, 32, 34, 62, 63, 72, 80, 87, RE, LE, AS, BC or AS1, may be followed by R, may be followed by additional letter(s) and/or number(s).

Type D4N, followed by blank, followed by 9, followed by 1, followed by 20, followed by GP.

Type D4JL, followed by 1, 2, 3 or 4, followed by A through H, J through N or P through R, followed by D or F, followed by A, G or K, followed by C or D, followed by 5, 6 or 7, followed by blank, followed by blank, Y or Z, may be followed by four alphanumeric code, may be followed by 6 digit maximum alphanumeric code.

Terminal relay, Model F3SP-T01.

Thermal overload relays, Cat. Nos. J7TL-D2, -E2, -F2, 7TL-D, -E, -F, -A, -B, -C.

(+) = Additional functional safety investigation was completed to UL 991 and IEC IEC 60947-5-3.

Trademark and/or Tradename: **OMRON** and/or **ST**

Last Updated on 2009-10-22

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2010 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up

Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2010 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.



OMRON AUTOMATION AND SAFETY • THE AMERICAS HEADQUARTERS • Chicago, IL USA • 847.843.7900 • 800.556.6766 • www.omron247.com

OMRON CANADA, INC. • HEAD OFFICE

Toronto, ON, Canada • 416.286.6465 • 866.986.6766 • www.omron247.com

OMRON ELECTRONICS DE MEXICO • HEAD OFFICE

México DF • 52.55.59.01.43.00 • 01-800-226-6766 • mela@omron.com

OMRON ELECTRONICS DE MEXICO • SALES OFFICE

Apodaca, N.L. • 52.81.11.56.99.20 • 01-800-226-6766 • mela@omron.com

OMRON ELETRÔNICA DO BRASIL LTDA • HEAD OFFICE

São Paulo, SP, Brasil • 55.11.2101.6300 • www.omron.com.br

OMRON ARGENTINA • SALES OFFICE

Cono Sur • 54.11.4783.5300

OMRON CHILE • SALES OFFICE

Santiago • 56.9.9917.3920

OTHER OMRON LATIN AMERICA SALES

54.11.4783.5300

OMRON EUROPE B.V. • Wegalaan 67-69, NL-2132 JD, Hoofddorp, The Netherlands. • +31 (0) 23 568 13 00 • www.industrial.omron.eu

Authorized Distributor:

Automation Control Systems

- Machine Automation Controllers (MAC) • Programmable Controllers (PLC)
- Operator interfaces (HMI) • Distributed I/O • Software

Drives & Motion Controls

- Servo & AC Drives • Motion Controllers & Encoders

Temperature & Process Controllers

- Single and Multi-loop Controllers

Sensors & Vision

- Proximity Sensors • Photoelectric Sensors • Fiber-Optic Sensors
- Amplified Photomicrosensors • Measurement Sensors
- Ultrasonic Sensors • Vision Sensors

Industrial Components

- RFID/Code Readers • Relays • Pushbuttons & Indicators
- Limit and Basic Switches • Timers • Counters • Metering Devices
- Power Supplies

Safety

- Laser Scanners • Safety Mats • Edges and Bumpers • Programmable Safety Controllers • Light Curtains • Safety Relays • Safety Interlock Switches