

●SAFETY PRECAUTIONS●

(Always read these precautions before using this equipment.)

Before using this product, please read this manual and the relevant manuals introduced in this manual carefully and pay full attention to safety to handle the product correctly.

The precautions given in this manual are concerned with this prod-

anual, the safety precautions are ranked as "WARNING" and "CAUTION".

GOT2000

Indicates that incorrect handling may cause MARNING hazardous conditions, resulting in death or severe injury.

IB(NA)-0800537ENG-B(1410)MEE

A CAUTION Indicates that incorrect handling may cause hazardous conditions, resulting in medium or slight personal injury or physical damage.

according to the circumstances. Always follow the instructions of both levels because they are impor-

Please save this manual to make it accessible when required and always forward it to the end user.

Note that the \triangle CAUTION level may lead to a serious accident

[DESIGN PRECAUTIONS]

⚠ WARNING

- Some failures of the GOT, communication unit or cable may keep the outputs on or off.

 Some failures of a touch panel may cause malfunction of the input objects such as a touch switch. such as a touch switch.

 An external monitoring circuit should be provided to check for output signal which may lead to a serious accident.

 Not doing so can cause an accident due to false output or malfunction.
- Do not use the GOT as the warning device that may cause a serious accident.
 An independent and redundant hardware or mechanical interlock is required to configure the device that displays and outputs serious warning. Failure to observe this instruction may result in an accident due to incorrect output or malfunction.
- The GOT backlight failure disables the operation on the touch switch(s). When the GOT backlight has a failure, the POWER LED blinks (orange/blue) and the display section dims. In such a case, the input by the touch switch(s) is disabled.
- and the display section drins, in such a case, the input by the fouch switch(s) is disabled.
 The display section of the GOT is an analog-resistive type touch panel,
 When multiple points of the display section are touched simultaneously, an
 accident may occur due to incorrect output or malfunction.
 Do not touch the display section in 2 points or more simultaneously,
 if you touch the display section simultaneously in 2 points or more, the switch
 that is located around the center of the touched point, if any, may operate.
 Doing so may cause an accident due to incorrect output or malfunction.
 When programs or parameters of the controller (such as a PLC) that is
 monitored by the GOT are changed, be sure to reset the GOT, or trum on the
 unit again after shutting off the power as soon as possible.
 Not doing so can cause an accident due to false output or malfunction.
 If a communication fault (including cable disconnection) occurs during
 monitoring on the GOT, communication between the GOT and PLC CPU is
 suspended and the GOT becomes inoperative.

- For bus connection: The GOT becomes inoperative.
 For other than bus connection: The GOT becomes inoperative.
 A system where the GOT is used should be configured to perform any significant operation to the system by using the switches of a device other than the GOT on the assumption that a GOT communication fault will occur. Not doing so can cause an accident due to false output or malfunction.

⚠ WARNING

- Products with the C.I., DIV.2 mark on the rating plate are suitable for use in Class I, Division 2, Groups A, B, C and D hazardous locations, or nonhazardous locations only. This mark indicates that the lammable gases, vapors, or liquids are not likely to exist under not be conditione. When using the products in the Class I, Division 2 environment, observe the following to reduce the risk of explosion.

 1 This device is open-type and is to be installed in an enclosure suitable for the environment and require a tool or key to open.

 1 Warning Explosion Hazard Substitution of any component may impair suitability for Class I, Division 2.

 1 Warning Explosion Hazard Do not disconnect equipment unless power has been removed or the area is known to be non-hazardous.

 1 The side interface and extension interface of this equipment cannot be used in Class I, Division 2 environments.
- Les produits marqués Cl.1, DIV.2 sur la plaque signalétique peuvent être utilisés en Class I, Division 2, local dangereux de groupe A, B, C et D, ou
- Les produits flariques chi. Div. 2 sin a piaque signaleulue peuvent eur et utilisés en Class I, Division 2, local dangereux de groupe A, B, C et D, ou uniquement en local non dangereux.

 Ce logo indique que le produit est homologué pour utilisation en environnement de Class I, Division 2 où, dans des circonstances anormales, il peut y avoir présence de gaz, vapeurs ou liquides inflammables.

 Sì le produit est utilisé en environnement de Class I, Division 2, observer les précautions suivantes pour réduire le risque d'explosion.

 Cet appareil est de type ouvert et il doit être installé dans une enceinte appropriée à l'environnement et ne pouvant être ouverte qu'au moyen d'une clé ou d'un outil.

 Avertissement Danger d'explosion Toute substitution de composant peut compromettre l'aptitude à l'utilisation en Class I, Division 2.

 Avertissement Danger d'explosion Ne pas déconnecter l'équipement quand le circuit est sous tension, ni avant de d'être assuré de l'absence d'atmosphère inflammable.

- quand le circuit est sous terisoni, in training de différent par de distinssiphé inflammable.

 L'interface latérale et l'interface d'extension de cet équipement ne peuvent être utilisées dans les environnements de Classe 1, Division 2.

△ CAUTION

- Do not bundle the control and com unication cables with main-circuit now or other wiring.

 Run the above cables separately from such wiring and keep them a minir of 100mm apart. of 100mm apart.

 Not doing so noise can cause a malfunction.
- Do not press the GOT display section with a pointed material as a pen or
- driver.

 Doing so can result in a damage or failure of the display section.

 When the GOT is connected to the Ethernet network, the available IP address is restricted according to the system configuration.

 •When multiple GOTs are connected to the Ethernet network:

 Do not set the IP address (192.168.3.18) for the GOTs and the controllers in the network.

 When a single GOT is connected to the Ethernet network:

 - stwork. a single GOT is connected to the Ethernet network : t set the IP address (192.168.3.18) for the controllers except the GOT
 - When a single GDT Is CURRENCE GENTED ON THE CONTROLLERS EXCEPT THE GOT IN THE NEW ACCOUNT. THE MEMORY AND THE STATE OF THE GOT IN THE CONTROLLERS AND THE GOT IN THE CONTROLLERS AND THE GOT IN THE CONTROLLERS AND THE CONTR
- system.

 Turn on the controllers and the network devices to be ready for communication before they communicate with the GOT.

 Failure to do so can cause a communication error on the GOT.

 When the GOT is subject to shock or vibration, or some colors appear on the screen of the GOT, the screen of the GOT might flicker.

[MOUNTING PRECAUTIONS]

△ WARNING

- Be sure to shut off all phases of the external power supply used by the system before mounting or removing the GOT main unit to/from the panel Not doing so can cause the unit to fail or malfunction.
- Be sure to shut off all phases of the external power supply used by the system before mounting or removing the option unit onto/from the GOT.

△ CAUTION

- Use the GOT in the environment that satisfies the general specifications described in this manual. Not doing so can cause an electric shock, fire, malfunction or product damage or deterioration.
- When mounting the GOT to the control panel, tighten the mounting screws in the specified torque range (0.36 N•m to 0.48 N•m) with a Phillips-head
- screwdriver No.2.
 Undertightening can cause the GOT to drop, short circuit or malfunction Overtightening can cause a drop, short circuit or malfunction due to the damage of the screws or the GOT.
- damage of the screws or the GOT, lighten the mounting screws in the following specified torque range. When mounting the communication unit or option unit other than wireless LAN unit to the GOT, fit it to the connection interface of the GOT and tighten the mounting screws in the specified torque range (0.38 N-m to 0.48 N-m) with a
- mounting screws in the specified torque range (0.36 N-m to 0.48 N-m) with a Philips-head screwdriver No.2. When loading the wireless LAN unit to the GOT, fit it to the side interface of GOT and tighten the mounting screws in the specified torque range (0.10 N-m to 0.14 N-m) with a Philips-head screwdriver No.1. When the GOT is installed vertically, its side interface is positioned on the bottom. To prevent the falling of the wireless LAN communication unit from the side interface, install or remove the unit while holding it with hands. Under tightening can cause the GOT to drop, short circuit or maffunction. Overtightening can cause a drop, failure or malfunction due to the damage of the screws or unit.

△ CAUTION

- When closing the USB environmental protection cover, fix the cover to the GOT by pushing the [PUSH] mark on the latch firmly to comply with the protective structure.
- move the protective film of the GOT.
 hen the user continues using the GOT with the protective film, the film may
 the removed.
- not be removed.

 Operate and store the GOT in environments without direct sunlight, high temperature, dust, humidity, and vibrations.

 When using the GOT in the environment of oil or chemicals, use the protective cover for oil. Fallure to do so may cause failure or malfunction due to the oil or chemical entering into the GOT.

[WIRING PRECAUTIONS]

△ WARNING

system before wiring. Failure to do so may result in an electric shock, product damage or malfunctions.

△ CAUTION

- Make sure to ground the FG terminal and LG terminal of the GOT power supply section to the protective ground conductors dedicated to the GOT with a ground resistance of 100 \(\Omega \) or less.

 When tightening the terminal screws, use a Phillips-head screwdriver No.2. Terminal screws which are not to be used must be tightened always at torque 0.5 N·m to 0.8 N·m.
 Otherwise there will be a danger of short circuit against the solderless terminals.
- terminals.

 Use applicable solderless terminals and tighten them with the specified torque. If any solderless spade terminal is used, it may be disconnected when the terminal screw comes loose, resulting in failure.
- Correctly wire the GOT power supply section after confirming the rated voltage and terminal arrangement of the product.

 Not doing so can cause a fire or failure

[WIRING PRECAUTIONS]

△ CAUTION

- Tighten the terminal screws of the GOT power supply section in the specified torque range (0.5 N-m to 0.8 N-m). Undertightening can cause a short circuit or malfunction. Overtightening can cause a short circuit or malfunction due to the damage of the screws or the GOT.
- Exercise care to avoid foreign matter such as chips and wire offcuts entering the GOT. Not doing so can cause a fire, failure or malfunction.
- the GOT. Not doing so can cause a fire, failure or malfunction. The module has an ingress prevention label on its top to prevent foreign matter, such as wire offcuts, from entering the module during wiring. Do not peel this label during wiring. Before starting system operation, be sure to peel this label because of heat dissipation.

 Plug the communication cable into the GOT interface or the connected onlint, and tighten the mounting screws and the terminal screws in the specified torque range. Undertightening can cause a short circuit or malfunction. Overtightening can cause a short circuit or malfunction. Overtightening can cause a short circuit or malfunction. Overtightening can cause a short circuit or malfunction due to the damage of the screws or unit.

 Plug the OnA/ACPU/Motion controller(A series) bus connection cable by inserting it into the connector of the connected unit until it *Clicks**.
- After plugging, check that it has been inserted snugly.

 Not doing so can cause a malfunction due to a contact fault.

TEST OPERATION PRECAUTIONS]

△ WARNING

Before performing the test operations of the user creation monitor screen (such as turning ON or OFF bit device, changing the word device current value, changing the settings or current values of the timer or counter, and changing the buffer memory current value), read through the manual carefully and make yourself familiar with the operation method. During test operation, never change the data of the devices which are used to perform significant operation for the system.

[STARTUP/MAINTENANCE PRECAUTIONS]

⚠ WARNING

- When power is on, do not touch the terminals. Doing so can cause an electric shock or malfunction. Correctly connect the battery connector Do not charge, disassemble, short-circuit, solder, or throw the battery into the fire Doing so will cau battery to produce heat, explode, or ignite, resulting in injury and fire.
- Before starting cleaning or terminal screw retiphening, always switch off the power externally in all phases. Not switching the power off in all phases can cause a unit failure or malfunction. Undertightening can cause a short circuit or malfunction. Overtightening can cause a short circuit or malfunction. Overtightening can cause a short circuit or malfunction due to the damage of the screws or unit.

△ CAUTION

- Do not touch the conductive and electronic parts of the unit directly Doing so can cause a unit malfunction or failure.
- Doing so can cause a unit manufactor or alarms.

 The cables connected to the unit must be run in ducts or clamped.

 Not doing so can cause the unit or cable to be damaged due to the dangling, motion or accidental pulling of the cables or can cause a malfunction due to a cable connection fault.
- when unplugging the cable connected to the unit, do not hold and pull from the cable portion. Doing so can cause the unit or cable to be damaged or car cause a malfunction due to a cable connection fault.

△ CAUTION

- Do not drop the module or subject it to strong shock. A module damage may
- Do not drop or give an impact to the battery mounted to the unit.

 Doing so may damage the battery, causing the battery fluid to leak inside the battery. If the battery is dropped or given an impact, dispose of it without
- using.

 Before touching the unit, always touch grounded metals, etc. to discharge static electricity from human body, etc.

 Not doing so can cause the unit to fail or malfunction.
- Use the battery manufactured by Mitsubishi Electric Corporation. Use of other batteries may cause a risk of fire or explosion. Dispose of used battery promptly. Keep away from children. Do not disassemble and do not dispose of in fire.

Reep away from children.Do not disassemble and do not dispose on in file. Be sure to shut off all phases of the external power supply before replacing the battery or using the dip switch of the terminating resistor.Not doing so car cause the unit to fail or malfunction by static electricity.

[TOUCH PANEL PRECAUTIONS]

△ CAUTION

- For the analog-resistive film type touch panels, normally the adjustment is not
- required. However, the difference between a touched position and the object position may occur as the period of use elapses. When any difference between a touched position and the object position occurs, execute the touch panel calibration.
- When any difference between a touched position and the object position occurs, other object may be activated.
 This may cause an unexpected operation due to incorrect output or malfunction.

[PRECAUTIONS WHEN THE DATA STORAGE IS IN USE]

⚠ WARNING

If the SD card is removed from drive A of the GOT while being accessed by the GOT, the GOT may stop processing data for about 20 seconds. The GOT cannot be operated during this period. The functions that run in the background including a screen updating, alarm, logging, scripts, and others are also interrupted. Since this interruption makes an impact to the system operation, it might cause failure After checking the light off of SD card access LED, remove the SD card.

△ CAUTION

- If the data storage is removed from the GOT while being accessed by the GOT, the data storage and files may be damaged Before removing the data storage from the GOT, check the SD card access LED, system signal, or others to make sure that the data storage is not accessed. When inserting a SD card into the GOT, make sure to close the SD card cover. Failure to do so causes the data not to be read or written.

- cover. Failure to do so causes the data not to be read or written. When removing the SD card from the GOT, make sure to support the SD card by hand as it may pop out. Failure to do so may cause the SD card to drop from the GOT, resulting in a failure or break. When inserting a USB device into a USB interface of the GOT, make sure to insert the device into the interface firmly. Failure to do so may cause the USB device to drop from the GOT, resulting in a failure or break. Before removing the USB device from the GOT, follow the procedure for removal on the utility screen of the GOT. After the successful completion cialog is displayed, remove the USB device by hand carefully. Failure to do so may cause the USB device to drop from the GOT, resulting in a failure or break.

[DISPOSAL PRECAUTIONS]

△ CAUTION

When disposing of this product, treat it as industrial waste. When disposing of batteries, separate them from other wastes according to the local regulations. (Refer to the GOT2000 Series User's Manual (Hardware) for details of the battery directive in the EU member states.)

[TRANSPORTATION PRECAUTIONS] **△** CAUTION

- When transporting lithium batteries, make sure to treat them based on the transport regulations. (Refer to the GOT2000 Series User's Manual (Hardware) for details of the regulated models.)
- regulated models.)

 Make sure to transport the GOT main unit and/or relevant unit(s) in the manner they will not be exposed to the impact exceeding the impact resistance described in the general specifications of this manual, as they are rescision devices.
- resistance described in the general specinications of this manual, as they are precision devices.

 Failure to do so may cause the unit to fail.

 Check if the unit operates correctly after transportation.

 When furnigants that contain halogen materials such as fluorine, chlorine, bromine, and iodine are used for disinfecting and protecting wooden packaging from insects, they cause malfunction when entering our products. Please take necessary precautions to ensure that remaining materials from furnigant do not enter our products, or treat packaging with methods other than furnigation (heat method).

 Additionally, disinfect and protect wood from insects before packing products.


3.2.1 For GOTs powered from the 100 to 240VAC power supply

		Specifications			
	Item	GT2512-STBA	GT2510-VTBA,	GT2508-VTBA,	
			GT2510-VTWA	GT2508-VTWA	
Power st	upply voltage	Power supply volt	age AC100 to 240\	/AC (+10%, -15%)	
Power frequency			50/60Hz ± 5%		
Мах. арр	parent power	80VA	80VA	70VA	
D	maximum load	35W or less	34W or less	31W or less	
Power	Stand alone	14W	12W	11W	
ption	Stand alone with backlight off	7W	7W	7W	
Inrush current		60A or less (2ms, operating ambient temperature 25, maximum load)			
Allowable momentary power failure time		20 ms or less (100VAC or more)			
Noise immunity		1,500Vp-p noise voltage, 1μ s noise width (when measuring with a noise simulator under 25 to 60Hz noise frequency)			
Dielectric	c withstand voltage	1500VAC for 1 min	nute across power to	erminals and earth	
Insulation resistance		10M or more across power terminals and earth by a 500V DC insulation resistance tester			
Applicable wire size		0.75[mm ²] to 2[mm ²]			
Applicable solderless terminal		Solderless termin	al for M3 screw RA' V2-N3A, FV2-N3A		
Applicable tightening torque (Terminal block terminal screw)		0.5[N•m] to 0.8[N•m]			

3.2.2 For GOTs powered from the 24VDC power supply

Item		Specifications			
		GT2512-STBD	GT2510-VTBD, GT2510-VTWD	GT2508-VTBD, GT2508-VTWD	
Power supply voltage		D	C24V (+25%, -20%	6)	
Power	maximum load	37W or less	33W or less	31W or less	
consum	Stand alone	13W	10W	8W	
ption	Stand alone with backlight off	6W	6W		
Inrush current		5A or less (20ms	, operating ambien maximum load)	t temperature 25,	
Allowable momentary power failure time		10 ms or less			
Noise immunity		500Vp-p noise voltage, $1\mu s$ noise width (when measuring with a noise simulator under 25 to 60Hz noise frequency)			
Dielectric withstand voltage		350VAC for 1 min	ute across power to	erminals and earth	
Insulation resistance		10M or more across power terminals and earth by a 500V DC insulation resistance tester			
Applicable wire size		0.75[mm ²] to 2[mm ²]			
Applicable solderless terminal		Solderless terminal for M3 screw RAV1.25-3, V2-S3.3, V2-N3A, FV2-N3A			
Applicable tightening torque (Terminal block terminal screw)		0.5[N•m] to 0.8[N•m]			

3.3 External Dimensions



Manual The following shows manuals relevant to this product.

Manual name	Manual number (Model code)
GOT2000 Series User's Manual (Hardware)	SH-081194ENG (1D7MJ5)
GOT2000 Series User's Manual (Utility)	SH-081195ENG

(1D7MJ6) For detailed manuals, refer to the PDF manuals stored in the DVD-ROM for the

Detailed Manual

Relevant Manuals For relevant manuals, refer to the Help or the PDF manuals stored in the DVD

The latest manuals are also available from MITSUBISHI ELECTRIC FA Globa

Website (http://www.MitsubishiElectric.co.jp/fa/). © 2014MITSUBISHI ELECTRIC CORPORATION

Before using the GOT

Connect the connector of the GOT to the connector of the battery.

Refer to the GOT2000 Series User's Manual (Hardware) for the connection

For details on the GOT specifications, installing instructions, wiring, maintenance and inspection, or checking procedure for the version and the compatible standard, refer to the GOT2000 Series User's Manual (Hardware).

Packing List


The GOT product package includes the following:

, , ,	
Description	Quantity
GT25	1
Battery (GT11-50BAT) (Attached to the GOT)	1
Installation fitting	4
GT25 General Description (This manual)	1
CTOE + H M THOP	1

1. FEATURES

- Abundant standard equipment
 Variety of connection with FA devices
 SD card interface compatible with the SDHC card having a large capacity and allowing high-speed communication
 Connection with various peripheral devices with the USB host
- Connection with various mproved usability
 Abundant troubleshooting Abundant troubleshooting
 Easy and clear screen creation
 PC-like operation screen
 Support for the vertical installation
 Enhanced compatibility with Mitsubishi FA devices
 Essy replacement]
 LeD backlight
 Various extended functions supported

2. Part Names and Settings



GT2510 1)2) 3)4)---16)6) GT2508 1)2) 10)11)12)

15)23)22)21)20) 19)

No.	Name	Description	
1)	Display screen	Displays the utility and the user-created screen.	
2)	Touch Pane	For operating the touch switches in the utility and the user- created screen	
3)	USB interface (Host/Front face)	For connecting a USB mouse, connecting a USB keyboard, data transfer, and data storage (connector type: TYPE-A) (Only GT2512-STBA/D, GT2510-VTBA/D and GT2508-VTBA/D)	
4)	USB interface (Device /Front face)	For connecting a personal computer (connector type: Mini B) (Only GT2512-STBA/D, GT2510-VTBA/D and GT2508-VTBA/D)	
5)	POWER LED	Lit in blue : Power is properly supplied. Lit in orange : Screen saving Blinks in orange/blue : Backlight failure Not lit : Power is not supplied	
6)	Unit installation fitting	Mounting fixtures for fixing the GOT to the control panel	
7)	Reset switch	Hardware reset switch	
8)	Installation switch	Used for OS installations at the GOT startup	
9)	SD card access LED	Lit: SD card mounted Blinking: SC card accessed No lit: SD card not mounted or SD card mounted (removable)	
10)	SD card interface	For installing a SD card	
11)	SD card cover	With a switching function for accepting and stopping the access to the SD card When the cover is opened: Access is prohibited When the cover is closed: Access is allowed	
12)	Battery holder	Houses the battery	
13)	Side interface	For installing a communication unit	
14)	USB interface (Host/Back face)	For connecting a USB mouse, connecting a USB keyboard, data transfer, and data storage (connector type: TYPE-A)	
15)	Hole for attaching a cable clamp	Hole for attaching a cable clamp for preventing USB cable from being pulled out (Recommended product: RSG-130-V0 made by KITAGAWA INDUSTRIES CO.,LTD)	
16)	Terminating resistor setting switch (Inside cover)	For switching on and off of the terminating resistor for the RS-422/485 communication port (Default (Off))	
17)	Extension interface	For installing a communication unit or an option unit	
18)	Vertical installation arrow mark	For the vertical installation, install the GOT so that the arrow points upward.	
19)	Power terminal	Power input terminal, LG terminal, FG terminal	
20)	Ethernet interface	For communicating with a controller or connecting a personal computer (connector type: RJ-45 (modular jack))	
21)	RS-232 interface	For communicating with a controller (Connector type: D sub 9-pin (male))	
22)	RS-422/485 interface	For communicating with a controller (Connector type: D sub 9-pin (female))	
23)	USB interface (Device/ Back face)	For connecting personal computers (connector type: Mini-B (Only GT2510-VTWA/D, GT2508-VTWA/D)	

3. Specifications

3.1 General Specifications

Item		Specifications				
Operating ambient temperature*1 Température ambiante de fonctionnement*1	0 to 55°C ^{*2} 0 à 55°C ^{*2}					
Storage ambient temperature	-20 to 60°C					
Operating ambient humidity	10 to 90% RH, non-condensing					
Storage ambient humidity		10	to 90% RH,	non-condens		
			Frequency	Acceleration	Half- amplitude	Sweep count
	Complian t with JIS	Under	5 to 8.4Hz	-	3.5mm	10 times each in X.
Vibration resistance	B 3502 and IEC	intermitten t vibration	8.4 to150Hz	9.8m/s ²	-	Y and Z directions
	61131-2	Under	5 to 8.4Hz	-	1.75mm	
		s vibration	8.4 to 150Hz	4.9m/s ²	-	-
Shock resistance	i i	3 time	es each in X	d IEC 61131- , Y and Z dire	ctions	, ,.
Operating atmosphere	No greasy fumes, corrosive gas, flammable gas, excessive conductive dust, and direct sunlight (Same as storage atmosphere)					
Operating altitude*3	2000 m (6562 ft) max.					
Installation location	Inside control panel					
Overvoltage category*4	II or less					
Pollution degree*5		2 or less				
Cooling method				cooling		
Grounding		Type D grounding (100Ω or less). Connect to panel if unable to ground.				

*1: The operating ambient temperature includes the temperature inside the enclosure of the control panel to which the GOT is installed.

La température ambiante de fonctionnement inclut la température à l'intérieur du boitier du tableau de commande sur lequel le GOT est installé. 'When mounting a MELSECNETH communication unit (GT15-J71LP23-25, GT15-J71BR13), or CC-Link communication unit (GT15-J71LP23-25, GT15-J71BR13), or CC-Link communication unit (GT15-J61BT13), the operating ambient temperature must be reduced \$\cap{c}_{\mathcal{C}}\$ against the maximum values described in general specifications. Lors du montage d'un module communication MELSECNET/H (GT15-J71LP23-25, GT15-J71BR13) ou du module de communication CC-Lin (GT15-J61BT13), la température ambiante de fonctionnement doit étre de 5°c par rapport aux valei

*3: Do not use or store the GOT under pressure higher than the atmospheric pressure of altitude 0m (0ft.). Failure to observe this instruction may cause a malfunction. Failure to observe this instruction may cause a malfunction. When an air purge is made inside the control panel by adding pressure, there may be a clearance between the surface sheet and the screen making it difficult to use the touch panel, or the sheet may come off.

assumed to be connected between the public electrical power distribution network and the machinery within the premises. Category II applies to equipment for which electrical power is supplied from fixed facilities. The surge voltage withstand level for up to the rated voltage of 300 V is 2500 V.
*5: This index indicates the degree to which conductive material is generated in the

*4: This indicates the section of the power supply to which the equipment is

environment where the equipment is used. In pollution degree 2, only non-conductive pollution occurs but temporary conductivity may be produced due to condensation. efer to the GOT2000 Series User's Manual (Hardware) for details on the performance

3.2 Power Supply Specifications

The following indicates the power supply specifications for GT25.

Note

Make sure to power on the unit more than 5 seconds after power-off.

4. EMC AND LOW VOLTAGE DIRECTIVE

For the products sold in European countries, the conformance to the EMC Directive, which is one of the European Directives, has been a legal obligation since 1996. Also, conformance to the Low Voltage.

Directive, another European Directives, has been a legal obligation since

1997.

Manufacturers who recognize their products must conform to the EMC and Low Voltage Directive are required to declare that their products conform to these Directives and put a "CE mark" on their products.

Authorized representative in Europe
Authorized representative in Europe is shown below.

Name : Mitsubishi Electric Europe BV
Address : Gothaer strase 8, 40880 Ratingen, Germany

4.1 Requirements to Meet EMC Directive

EMC Directives are those which require "any strong electromagnetic force is not output to the external. Emission (electromagnetic interference)" and "It is not influenced by the electromagnetic wave from the external. Immunity (electromagnetic sensitivity)" ltems4.1.1 through4.1.3 summarize the precautions to use GOT and configure the mechanical unit in order to match the EMC directives. Though the data described herein are produced with our best on the basis of the requirement items and standards of the restrictions gathered. basis of the requirement items and standards of the restrictions gathered by Mitsubishi, they do not completely guaranteed that all mechanical unit manufactured according to the data do not always match the above.

4.1.1 EMC directive

Applied standard	Test standard	Test details	Standard value
	CISPR16-2-3 Radiated noise*1	Electromagnetic emissions from the product are measured.	30M-230MHz QP: 30dB _H V/m (30m in measurement range) ^{2, *3} 230M-1000MHz QP: 37dB _H V/m(30m in measurement range) ^{*2, *3}
	CISPR16-2-1 Conducted noise*1	Electromagnetic emissions from the product to the power line is measured.	150k-500kHz QP:79dB, Mean: 66dB ^{*2} 500k-30MHz QP:73dB, Mean: 60dB ^{*2}
	IEC61000-4-2 Electrostatic immunity*1	Immunity test in which static electricity is applied to the cabinet of the equipment.	± 4kV Contact discharge ± 8kV Aerial discharge
	IEC61000-4-3 Radiated electromagnetic field AM modulation	Immunity test in which field is irradiated to the product.	80-1000MHz:10V/m 1.4-2GHz:3V/m 2.0-2.7GHz:1V/m 80%AM modulation@1kHz
	IEC61000-4-4 Fast transient burst noise*1	Immunity test in which burst noise is applied to the power line and signal lines.	Power line:2kV Digital I/O(24V or higher): 1kV (Digital I/O(24V or less))> 250V (Analog I/O, signal lines)> 250V
EN61131-2 : 2007	IEC61000-4-5 Surge immunity ¹¹	Immunity test in which lightening surge is applied to the product.	AC power type Power line (between line and ground): ±2kV Power line (between lines) : ±1kV Data communication port : ±1kV DC power type Power line (between lines and ground): ±0.5kV Power line (between lines) : ±0.5kV Data communication port : ±1kV
	IEC61000-4-6 Conducted RF immunity*1	Immunity test in which a noise inducted on the power and signal lines is applied.	Power line: 10V Data communication port: 10V
	IEC61000-4-8 Power supply frequency magnetic field immunity	Test for checking normal operations under the circumstance exposed to the ferromagnetic field noise of the power supply frequency (50/60Hz).	30 A/m
	IEC61000-4-11 Instantaneous power failure and voltage dips immunity	Test for checking normal operations at instantaneous power failure.	AC power type 0.5 cycle 0% (interval 1 to 10s) 250/300 cycle 0% 10/12 cycle 40% 25/30 cycle 70%

 * 3: The above test items are conducted in the following conditions. 30M-230MHz QP : 40dB $_{\! H}$ V/m (10m in measurement range) 230M-1000MHz QP : 47dB $_{\! H}$ V/m (10m in measurement range)

4.1.2 Control panel

The GOT is an open type device (device installed to another device) and must be installed in a conductive control panel. It not only assure the safety but also has a large effect to shut down the noise generated from GOT, on the control panel (1) Control Panel

(a) The control panel must be conductive

(b) When fixing a top or bottom plate of the control panel with bolts, do not coat the plate and bolt surfaces so that they will come into

And connect the door and box using a thick grounding cable in order to ensure the low impedance under high frequency. (c) When using an inner plate to ensure electric conductivity with the

control panel, do not coat the fixing bolt area of the inner plate and control panel to ensure conductivity in the largest area as

(d) Ground the control panel using a thick grounding cable in order to

ensure the low impedance under high frequency.

(e) The diameter of cable holes in the control panel must be 10cm (3.94in.). In order to reduce the chance of radio waves leaking out, ensure that the space between the control panel and its door is small as possible.

Paste the EMI gasket directly on the painted surface to seal the space so that the leak of electric wave can be suppressed.

Our test has been carried out on a panel having the damping characteristics of 37dB max. and 30dB mean (measured by 3m

method with 30 to 300MHz).

(2) Connection of power and ground wires
Ground and power supply wires for the GOT must be connected as described below.

(a) Provide a grounding point near the GOT. Short-circuit the LG and FG terminals of the GOT (LG: line ground, FG: frame ground) and ground them with the thickest and shortest wire possible (The wire length must be 30cm (11.81in.) or shorter.)

The LG and FG terminals function is to pass the noise generated in the PC system to the ground, so an impedance that is as low as possible must be ensured. As the wires are used to relieve the noise, the wire itself carries a large noise content and thus short wiring means that the wire is prevented from acting as an

Note) A long conductor will become a more efficient antenna at

high frequency. (b) The earth wire led from the earthing point must be twisted with $% \left(\frac{1}{2}\right) =\frac{1}{2}\left(\frac{$ the power supply wires.

By twisting with the earthing wire, noise flowing from the power supply with the earthing wire, noise flowing from the power supply with the earthing wire, noise flowing from the power supply with the earthing wire, noise flowing from the power supply with the earthing wire, noise flowing from the power supply with the earthing wire, noise flowing from the power supply wires.

supply wires can be relieved to the earthing. However, if a filter is installed on the power supply wires, the wires and the earthing wire may not need to be twisted


4.1.3 Noise filter (power supply line filter)

The noise filter (power supply line filter) is a device effective to reduce conducted noise. Except some models, installation of a noise filter onto the power supply lines is not necessary. However conducted noise can be reduced if it is installed. (The noise filter is generally effective for reducing conducted noise in the band of 10MHz or less.) Usage of the following filters is recommended.

Model name	FN343-3/05	FN660-6/06	RSHN-2003
Manufacturer	SCHAFFNER	SCHAFFNER	TDK
Rated current	3A	6A	3A
Rated voltage		250V	•

The precautions required when installing a noise filter are described

(1) Do not install the input and output cables of the noise filter together to prevent the output side noise will be inducted into the input side cable where noise has been eliminated by the noise filer.



(2) Connect the noise filter's ground terminal to the control panel with the shortest cable as possible (approx. 10cm (3.94 in.) or less)

4.2 Requirements for Compliance with the Low **Voltage Directive**

The Low Voltage Directive requires each device which operates with power supply ranging from 50VAC to 1000V and 75VDC to 1500V to satisfy necessary safety items.

In the Sections from 4.2.1 to 4.2.5, cautions on installation and wiring of the GOT to conform to the Low Voltage Directive requires are described.

We have put the maximum effort to develop this material based on the requirements and standards of the Directive that we have collected. However, compatibility of the devices which are fabricated according to the contents of this manual to the above Directive is not guaranteed. Each manufacturer who fabricates such device should make the final judgement about the application method of the Low Voltage Directive and the product compatibility.

4.2.1 Standard subject to GOT

Standard applied to GOT:

EN61131-2 Programmable controllers - Equipment requirements and tests

EN60950-1 Safety of Information Technology Equipment


4.2.2 Power supply

The insulation specification of the GOT was designed assuming installation category II. Be sure to use the installation category II power supply to the GOT.

The installation category indicates the durability level against surge voltage generated by lightning strike.

Category I has the lowest durability; category IV has the highest

durability



Installation category

Category II indicates a power supply whose voltage has been reduced by two or more levels of isolating transformers from the public power distribution.

4.2.3 Control panel

Because the GOT is open type equipment (device designed to be stored within another device), be sure to use it only when installed in a control

(1) Shock Protection

In order to prevent those who are unfamiliar with power facility, e.g., an operator, from getting a shock, make sure to take the following measures on the control panel.

(a) Store the GOT within the control panel locked, and allow only those who are familiar with power facility to unlock the panel.

(b) Build the structure in order that the power supply will be shut off when the control panel is opened.

(2) Dustproof and waterproof features

The control panel also provides protection from dust, water and other substances. Insufficient ingression protection may lower the insulation withstand voltage, resulting in insulation destruction. The insulation in the OOT is designed to cope with the pollution level 2, so use in an environment with pollustion level 2 or better

Pollution level 1: An environment where the air is dry and conductive dust does not exist.

Pollution level 2: An environment where conductive dust does not usually exist, but occasional temporary conductivity occurs due to the accumulated dust.

Generally, this is the level for inside the control panel equivalent a control room or on the floor of a typical factory.

An environment where conductive dust exits and Pollution level 3: conductivity may be generated due to the accumulated

An environment for a typical factory floor. Continuous conductivity may occur due to rain, snow etc. An outdoor environment. Pollution level 4:

4.2.4 Grounding

The following are applicable ground terminals. Use them in the grounded Be sure to ground the GOT for ensuring the safety and complying with the EMC Directive.

Functional grounding \perp : Improves the noise resistance

4.2.5 External wiring

(1) External devices When a device with a hazardous voltage circuit is externally connected to the GOT, select a model which complies with the

Low Voltage Directive's requirements for isolation between the primary and secondary circuits.

(2) Insulation requirements

Dielectric withstand voltages are shown in the following table Reinforced Insulation Withstand Voltage (Installation Category II, source : IEC664)

Rated voltage of hazardous voltage area	Surge withstand voltage (1.2/50 µs)
150 VAC or below	2500V
300 VAC or below	4000V


5. INSTALLATION

Control Panel Inside Dimensions for Mounting GOT

Install the GOT on the control panel out of the way for the equipment inside the control panel. Do not install the GOT and the unit in prohibited areas for the installation.

Applicable cable
Some cables may need to be longer than the specified dimensions when connecting to the
GOT. Therefore, consider the connector dimensions and bending radius of the cable as

5.2 Panel Cutting Dimensions



5.3 Mounting Position

When mounting the GOT, the following clearances must be maintained from other structures and devices.


Some cables may need to be longer than the specified dimensions when

connecting to the GOT.

Therefore, consider the connector dimensions and bending radius of the cable as well for installation.

For the lead-in allowance for cables at the bottom of the GOT, refer to the GOT2000 Series User's Manual (Hardware)

For the vertical installation, install the GOT so that the vertical installation arrow printed on the GOT rear face points upward.



According to the dimensions in the following table, leave clearances between the GOT and the other devices. The values enclosed in square brackets apply to the case where no other equipment generating radiated noise (such as a contactor) or heat is installed near the GOT. However, keep the ambient temperature of the GOT to 55°C or lower

Item 48(1.89) or 48(1.89) or more GOT only [18(0.71) or more] [29(1.14) or 23(0.91) or 48(1.89) or more [18(0.71) or more] Bus connection unit is fitted [29(1.14) o more] 48(1.89) or more[18(0.71) or more] CC-Link communication unit (GT15-J61BT13) fitted 48(1.89) or more[18(0.71) or more] 18(1.89) or 48(1.89) or MELSECNET/H communica-67(2.64) o [45(1.77) or [38(1.50) or MELSECNET/H comm 48(1.89) or more[18(0.71) or more] unit(optical) fitted*2 CC-Link IE Controller Network 48(1.89) or more[18(0.71) or more] communication unit fitted CC-Link IE Field Network of 48(1.89) or more[18(0.71) or more] Printer unit fitted External I/O unit fitted Sound output unit fitted Horizontal: 78(3.07) or mo [18(0.71) or more] Vertical: 48(1.89) or mor [18(0.71) or more] When the SD card is used When the SD card is not used 50(1.97) or more[20(0.79) or more] Horizontal: 50(1.97) or more [20(0.79) or more] Vertical: 80(3.15) or more [20(0.79) or more]


- *1: This value is for use of the coaxial cable 3C-2V (JIS C 3501) For specifications of the cable, refer to the GOT2000 Series Connection
- Manual for a controller used. *2: This value differs depending on the cable used
- *3: When opening or closing the battery cover: 72(2.83) or more

Control Panel Inside Temperature and **Installation Angle** When installing the GOT to a panel, set the display section as shown below. Using the GOT with the installation angle other than the following

deteriorates the GOT earlier. Installing the GOT horizontally When installing the GOT with the installation angle between 60 to 105 %, the temperature inside the control panel must be within 55 °C.

When installing the GOT with the installation angle other than between 60 to 105°, the temperature inside the control panel must be Installing the GOT vertically

When the GOT is installed a 90° angle, the control panel inside temperature must be within 55°C. When the GOT is installed at any angle other than 90°, the control panel inside temperature must be within 40°C




5. INSTALLATION

5.1 Dimensions intérieures du tableau de commande pour le montage du GOT

Installez le GOT sur le tableau de commande en laissant de l'espace pour le dispositif à l'intérieur du tableau de commande. N'installez pas le GOT et le module dans des zones où l'installation est interdite

Point	
connexion au	ble es peuvent être plus longs que les dimensions spécifiées lors de la GOT. Par conséquent, prenez également en compte les dimensions du t le rayon de courbure du câble pour l'installation.


5.2 Cotes de découpe du panneau



5.3 Position de montage

Lors du montage du GOT, laissez les espaces suivants pour les autres structures et dispositifs. Certains câbles peuvent être plus longs que les dimensions spécifiées lors de la connexion au GOT. Par conséquent, prenez également en compte les dimensions du connecteur et le rayon de courbure du câble pour l'installation.

Pour connaître l'espace à laisser pour les câbles sous le GOT, référez-vous au manuel GOT2000 Series User's Manual (Hardware). Pour l'installation à la verticale, installez le GOT de sorte que la flèche d'installation à la verticale imprimée sur la face arrière du GOT pointe vers le haut.



Laissez les espaces entre le GOT et les autres dispositifs en fonction des dimensions contenues dans le tableau suivant. Les valeurs entre parenthèses s'appliquent au cas où aucun dispositif générant des émissions sonores (comme un contacteur) ou de la chaleur n'est ins . Toutefois, maintenez la température ambiante du GOT à 55°C ou moins

GOT uniquement
Unité de connexion de bus encastrée Unité de connexion série encastrée Unité de connexion série encastrée Module de communication CC-Link (GT15-J61BT13) encastré Module de communication MELSECNET/H (coaxial) encastré 1 Module de communication plus [38 (1.50) ou plus[18 (0.71) ou plus] 67 (2.64) ou plus [45 (1.77) ou plus] Module de communication plus [38 (1.50) ou plus] 67 (2.64) ou plus [45 (1.77) ou plus]
encastrée 48 (1,89) ou plus[18 (0,71) ou plus]
Link (GT15-J618T13) encastré 48 (1.89) ou plus[18 (0.71) ou plus]
Module de communication MELSECNET/H (coaxial) encastré¹1 Module de communication plus plus 57 (2,64) ou plus 58 (1,77)
MELSECNET/H (optique) 48 (1,89) ou plus[18 (0,71) ou plus] encastré ²
Module de communication réseau de contróleur CC-Link IE 48 (1,89) ou plus[18 (0,71) ou plus] encastré
Module de communication réseau de champ CC-Link IE encastré 48 (1,89) ou plus[18 (0,71) ou plus]
Imprimante encastrée 48 (1,89) ou plus[18 (0,71) ou plus]
Module d'E/S externe encastré 48 (1,89) ou plus[18 (0,71) ou plus]
Module de sortie acoustique encastré 48 (1,89) ou plus[18 (0,71) ou plus]
Horizontal: 78 (3,07) ou plus
[18 (0,71) ou plus]
Vertical: 48 (1,89) ou plus [18 (0,71) ou plus]
[10 (0,11) ou plus]

	Article	GT2512 GT2510		GT2508
		50 (1,97) ou plus		
Ŭ	Quand la carte SD n'est pas utilisée	50 (1,97) ou plus[20 (0,79) ou plus]		
D		Horizontal: 50 (1,97) ou plus [20 (0,79) ou plus] Vertical: 80 (3,15) ou plus [20 (0,79) ou plus]		
Е	.3	100 (3,94) ou plus[20 (0,79) ou plus]		

- *1 : Cette valeur est utilisée pour le câble coaxial 3C-2V (JIS C 3501). Pour connaître les spécifications du câble, référez-vous au manuel GOT2000 Series Connection Manual for a controller used.
- Cette valeur diffère selon le câble utilisé. *3 : Pour ouvrir ou fermer le couvercle de la batterie : 72 (2,83) ou plus


5.4 Température intérieure et angle d'installation du tableau de commande

Lors de l'installation du GOT sur un panneau, réglez la zone d'affichage comme indiqué ci-dessous. Si l'angle d'installation est différent de celui indiqué, le GOT se détériore

plus tôt. Installation du GOT à l'horizontale

Staliation du GOT avec un angle d'installation compris entre 60 et 105°, la température à l'intérieur du tableau de commande doit être d'environ 55°C. Lors de l'installation du GOT avec un angle d'installation non compris entre 60 et 105°, la température à l'intérieur du tableau de commande doit être d'environ 40°C. Installation du GOT à la verticale Lors de l'installation du GOT avec un angle de 90°, la température à

l'intérieur du panneau de commande ne doit pas dépasser 55°C. Lors de l'installation du GOT avec tout autre angle que 90°, la températt à l'intérieur du panneau de commande ne doit pas dépasser 40°C.



6. MAINTENANCE AND INSPECTION

nance and inspection for the GOT

Warranty

Mitsubishi will not be held liable for damage caused by factors found not to be the cause of Mitsubishi; machine damage or lost profits caused by faults in the Mitsubishi products; damage, secondary damage, accident compensation caused by special factors unpredictable by Mitsubishi; damages to products other than Mitsubishi products; and to other duties.

⚠ For safe use This product has been manufactured as a general-purpose part for

- general industries, and has not been designed or manufactured to be incorporated in a device or system used in purposes related to Before using the product for special purposes such as nuclear
- power, electric power, aerospace, medicine or passenger movement vehicles, consult with Mitsubishi.

 This product has been manufactured under strict quality control.
- However, when installing the product where major accidents or losses could occur if the product fails, install appropriate backup or failsafe functions in the system.

Mitsubishi Electric Automation Inc. 500 Corporate Woods Parkway Vernon Hills, IL 60061, U.S.A. Tel:+1-847-478-2100

ar

Country/Region Sales office/Tel

ectric Europe B.V. UK Branch ne, Hatfield, Hertfordshire., AL10 8XB, U.K. Milsubishi Electric Europe B.V. Italian Branch Centro Dir. Colleoni, Pal. Perseo-Ingr.2 Via Paracelso 12, I-20041 Agrate Brianza., Milano, Italy Tel: +39-039-60531

Mitsubishi Electric Europe B.V. Spanish Branch Carretera de Rubi 76-80, Carretera de Rubi 76-80, E-08190 Sant Cugat del Valles, Barcelona, Spain Tel: +34-93-565-3131 Mitsubishi Electric Europe B.V. French Branch 25, Boulevard des Bouvets, F-92741 Nanterre Cedex, France Tel: +33-1-5568-5568

stries Ltd Private Bag 2016, ZA-1600 Isando, South Africa Tel: +27-11-928-2000

Tel: +27-11-928-2000
Mitsubishi Electric Automation (Hong Kong) Ltd.
10th Floor, Manulife Tower, 169 Electric
Road, North Point, Hong Kong
Tel: +852-2887-8870
Mitsubishi Electric Automation (China) Ltd.
4/F Zhi Fu Plazz, No.80 Xin Chang Road,
Shanghai 200003, China
Tel: +86-21-6120-0808
Setsuvo Enterprise Co., Ltd. Hong Kong

Setsuyo Enterprise Co., Ltd. 6F No.105 Wu-Kung 3rd.Rd, Wu-Ku Hsiang, Taliyah Hsine, Taiwan Tel: +886-2-2299-2499 Mitsubishi Electric Automation Korea Co., Ltd nation Korea Co. Ltd. Korea

1480-6, Gayang-dong, Gangseo-ku Seou 157-200, Korea

157-200, Korea
Tel: +82-2-3660-9552
Mitsubishi Electric Asia Pte, Ltd.
307 Alexandra Road #05-01/02,
Mitsubishi Electric Building, Singapore 159943
Tel: +65-6470-2460
Mitsubishi Electric Automation (Thailand) Co., Ltd. Singapore

Thailand Mitsubishi Electric Automation (Thailand) Co., Ltd.
Bang-Chan Industrial Estate No.111 Moo 4, Serithai Rd,
T.Kannayao, A.Kannayao, Bangkok 10230 Thailand
Tel: +66-2-517-1326
P.T. Autoteknindo Sumber Makmur
Muara Karang Selatan, Block A/Utara
No.1 Kaw. No.11 Kawasan Industri Pergudangan
Jakarta - Utara 14440, P.O.Box 5045 Jakarta, 11050 Indonesia

Tel: +62-21-6630833 India Messung Systems Pvt, Ltd. Electronic Sadan NO:III Unit No15, M.I.D.C Bhosari, Pune-411026, India
Tel: +91-20-2712-3130
Mitsubishi Electric Australia Pty. Ltd.
348 Victoria Road, Rydalmere, N.S.W 2116, Australia
Tel: +61-2-9684-7777

AMITSUBISHI ELECTRIC CORPORATION

HEAD OFFICE : TOKYO BUILDING, 2-7-3 MARUNOUCHI, CHIYODA-KU, TOKYO 100-8310, JAPAN NAGOYA WORKS : 1-14, YADA-MINAMI 5-CHOME, HIGASHI-KU, NAGOYA, JAPAN

of Economy, Trade and Industry for service transaction permission. Specifications subject to change without notice

Printed in Japan, October 2014

be installed in a conductive control panel.

The above test items are conducted in the condition where the GOT is installed on the conductive control panel and combined with the Mitsubishi PLC.

*2: QP (Quasi-Peak): Quasi-peak value, Mean: Average value